

B5V MR (non-magnetic) Fire Extinguisher

Part number 25078

Electrical risks

Rechargeable

UL Rated 5-B:C



Description

The 5 lb. Badger Carbon Dioxide Fire Extinguisher is manufactured using special components. It has been independently tested and has received the MR Conditional Rating. Suitable for use on the following types of fire:

- Class B (liquids)
- Class C fires (energized electrical equipment)

B5V MR

Features

- Recommended for use in and around MRI rooms
- Easy-to-pull safety pin
- Stainless steel handle & lever
- Chrome plated brass valve assembly
- 5 lb. of fire extinguishing agent (Average)
- 6 year limited warranty
- Approved wall hanger & screws
- Clean white powder coated cylinder for corrosion protection
- Heavy duty aluminum D.O.T. specification cylinder
- Carbon Dioxide is a clean extinguishing agent that does not leave any residue to damage equipment



MR CONDITIONAL

This extinguisher has been tested in a 3 Tesla MR imaging system and found to pose no magnetic safety hazards.

MR Extinguisher Markings Conform to New FDA Recommendations Contained in ASTM-2503-05 "Standard for Marking Medical Devices and Other Items for Safety in Magnetic Resonance Environments".

At a Glance

- Model B5V MR
- Carbon dioxide
- UL listed
- UL rated 5-B:C
- Tested MR Conditional
- Supplied with wall hanger
- 5 year limited warranty
- Suitable for use on energized electrical equipment

For use on the following types of fire:



Product Specification

Net agent weight (Average)	5 lb.
Unit weight (Average)	15.0 lb.
Diameter	5.25 inches
Height	17.0 inches
Discharge time	9 seconds
Discharge range	3-8 feet
Operating pressure	850 psi @ 70°F
Cylinder	Aluminum
Valve, handle, lever	Brass & stainless steel
Wall Hanger	Included

Packaging Options



SINGLE PACK

Badger Fire Protection

4251 Seminole Trail, Charlottesville, Virginia 22911 • 1.800.446.3857 • www.badgerfire.com

