

# Badger

Fire Protection

## Purple K Dry Chemical



Badger's high performance Purple K dry chemical stored pressure fire extinguishers are designed for use on high-hazard Class B and C fires. They are generally superior to other dry chemicals, making them ideal for use in industrial and commercial premises where there is a flammable liquid risk.

They mount on any surface with wall hook or if preferred, can be supplied with optional vehicle bracket.

### Features

- Available in four sizes, 2½ lb, 5 lb, 10 lb & 20 lb
- Chrome plated brass valves
- Stainless steel handle, lever, and hose band
- Color coded labels for instant type recognition
- Re-designed label incorporating easy to follow instructions and larger fire pictograms
- Operate effectively at both high and low temperatures
- Epoxy coated steel cylinders to resist corrosion, dents and punctures
- 12 year interval between hydrotests
- USCG approved

UL listed  
Six year warranty



Models:  
 B250P  
 B5P  
 B5P-B  
 B10P  
 B20P



## Specifications

Model Number	B250P	B5P	B5P-B	B10P	B20P
Nominal Capacity (lbs)	2.5	5	5	10	20
Nominal Capacity (kilograms)	1.13	2.27	2.27	4.54	9.07
UL Fire Rating	10B:C	30B:C	30B:C	80B:C	120B:C
Agent Type	Purple K	Purple K	Purple K	Purple K	Purple K
Item Part Number	23485	23488	23491	23778	23495
Valve Material	Plated Brass	Plated Brass	Plated Brass	Plated Brass	Plated Brass
Shell Material	Steel	Steel	Steel	Steel	Steel
Shipping weight (lbs)	5.8	10.4	11	18	33
Shipping weight (kilograms)	2.65	4.7	5	8.16	15
Operating Pressure	195 PSI	195 PSI	195 PSI	195 PSI	195 PSI
Temperature Range (°F)	-40° To 120°	-40° To 120°	-40° To 120°	-40° To 120°	-40° To 120°
Discharge Time (seconds)	9.5	12	12	22	28
Discharge Range (feet)	10-15	12-18	12-18	16-20	16-20
Discharge Range (meters)	3.1-4.6	3.7-5.5	3.7-5.5	4.9-6.1	4.9-6.1
Unit Height (inches)	14.875	15.25	15.25	18.93	21.12
Unit Height (centimeters)	37.78	38.7	38.7	47.9	53.6
Unit Width (inches)	5.5	7.25	7.25	9.75	9.25
Unit Width (centimeters)	13.97	18.41	18.41	19.7	23.5
Shell Diameter (inches)	3	4.25	4.25	5.25	7.25
Shell Diameter (centimeters)	7.62	10.8	10.8	13.33	18.41
USCG Approval	YES	YES	YES	YES	YES
USCG Bracket	MB-250 Included	MB-5 Optional	MB-5 Included	MB-10 Optional	UB-20 Optional

BFPN0006

**Badger**

Fire Protection

4251 Seminole Trail  
 Charlottesville, VA 22911  
 Tel. (800) 446-3857  
 Fax. (800) 248-7809  
[www.badgerfire.com](http://www.badgerfire.com)